

Scotch™ 233+ Performance Masking Tape

**General
Description**

Scotch 233+ Performance Masking Tape is the premium creped paper masking tape designed to meet the critical masking requirements of the professional painter. Every feature of this tape is perfectly balanced to give a high performance masking result indoors and outdoors.

Scotch 233+ Performance Masking Tape is designed to give excellent moisture and solvent resistance to automotive paints. It has a state of the art and newly formulated adhesive that provides excellent instant adhesion and holding power yet allows for clean removal.

This tape is ideally suited for the automotive paint refinish industry.

Product Features

<i>Colour:</i>	Green
<i>Backing:</i>	Smooth creped paper treated with a temperature and solvent resistant saturant and coated with a backside sealant.
<i>Adhesive:</i>	Proprietary adhesive

Physical Properties

<i>Adhesion to steel:</i>	37 N/100mm
<i>Tensile strength:</i>	403 N/100mm
<i>Elongation at break:</i>	12%
<i>Temperature range:</i>	Up to 121°C for 30 minutes
<i>Thickness:</i>	0.17mm

Specific Products

<i>Width:</i>	3mm and 6mm
<i>Roll Length</i>	55m
<i>Width:</i>	12mm, 18mm, 24mm, 36mm, 48mm
<i>Roll Length</i>	50m

Application

1. Ensure surfaces are clean and dry before applying tape.
2. Apply firm pressure to the tape upon application.
3. Lay tape into depressions.
4. Remove tape before the paint dries thoroughly.
5. Remove tape at a moderate speed and at a 90° angle to the substrate.
6. The ideal removal temperature is 15 to 35°C.
7. Exposure of tape to prolonged periods of sunlight or outdoor weathering will make clean removal difficult. Variation will depend on the time of year and the taped surface.
8. Do not expose to temperatures above 121°C.

Storage

Store in a dry location, out of direct sunlight and away from all sources of heat. Ideal conditions are 20°C and 50% relative humidity. Storage in roll form for more than 12 months is not recommended.