



## 5830 DelicateMASK™ TAPE DATA SHEET

### DESCRIPTION

5830 DelicateMASK™ is a flexible crepe paper masking tape especially designed for second coat painting. It is a low tack tape making it ideal for use varnishes. DelicateMASK™ can be removed easily, leaving no residue on most surfaces. Care should be taken if DelicateMASK™ is being used on glass.

**5830 is designed as a low tack tape. It should be removed within 3 days of application. However, under some conditions the low tack of the adhesive may cause premature delamination of the tape from the surface. Under any conditions the tape should be removed as soon as the paint is fully cured.**

### SPECIFICATIONS

<b>Backing:</b>	Purple Crepe paper
<b>Average Thickness of Paper:</b>	0.116 mm
<b>Roll Length:</b>	50 metres
<b>Tack:</b>	Low
<b>Adhesion to Steel (ASTM 3330):</b>	>1.0gm per 25mm width
<b>Tensile Strength (ASTM 3759):</b>	1.1 g per 25mm width
<b>Elongation (ASTM 3759):</b>	4%

### APPLICATIONS

- Professional and domestic use
- Second coat applications
- Up to 3 day mask
- Masking for drywall, wallpaper and other delicate surfaces

*The conditions under which this product is stored affect its performance. Storage should be in dry, well ventilated rooms with a reasonably consistent temperature around 20°C and protected from continuous exposure to direct sunlight. The product should always be applied to clean, dry and grease free surfaces.*

*The information supplied is accurate to the best of our knowledge and is based on current data. Properties quoted are typical and do not therefore, constitute a specification. Customers are recommended to complete their own assessment of the product for its intended application under their own conditions. Please refer to the Conditions of Sale for further information.* **Aug 2003**



The Sellotape Company  
**A Division of Henkel  
New Zealand Limited**  
9 Astley Avenue, New Lynn  
Auckland, New Zealand

PO Box 2484, Auckland  
Phone: 09 827 6039  
Freephone: 0508 735 568  
Fax: 09 827 5114  
www.henkel.com

